TEL: 800-289-1539 FAX: 877-842-5126 E-MAIL: info@displays4sale.com

# **Product Sheet**

Item ID # TLES-1422

### 14x22 Frame Euro-Style Top / Side Load - Poster Frame Sign Holder Slide In Frame Design

## FOR CURRENT PRICING, VISIT THE ID # LISTED ABOVE

FREE SHIPPING









#### Product Details

- 14x22 Frame
- Wall Sign Holder and Poster Frame
- Easy Slide-in Frame Design
- Accepts 14x22 poster and sign sizes
- Quick-Change Sign Frame 14x22
- Your Choice of Top or Side loading 14x22 poster changes Euro-Style Metal Frame Profile: 1 3/16" Wide
- Narrow frame design has 3/4" overall off the wall depth
- Slot Opening: 7/16" (max insert thickness)
- Frame size is slightly larger than the 14x22 poster inserts
- Viewable Area: Moulding overlaps poster insert by 1/2" all around
- 2 Aluminum frame finishes available
- Frames can mount either Portrait or Landscape
- No Tools! Top or Side removable cap secures your insert material Installs Easily: Punched holes in frame allow for easy surface mounting
- Hanging hardware screws are included
- Top Load display frames 14 x 22 for INDOOR or OUTDOOR use
- Call to Customize Euro Top Load Poster Display and Sign Frames

#### **Ordering Options**

- Frame 14x22 Orientation: Portrait or Landscape
- Backing Board: 3/16" thick white coroplast (provides rigidiy to your poster)
- (this is recommended if your poster is not mounted)

#### Acrylic Window

(backer board & acrylic are used to sandwich your insert)

- Clear Acrylic (.040 Thickness)...(See Pricing)
- Strong lightweight acrylic provides a clear viewing window
  - Non-Glare (.060 Thickness)...(See Pricing)
- Reduces glare from natural or artificial light
  - Break Resistant (.080 Thickness)...(See Pricing)
- High Impact acrylic, perfect for high traffic or public environments

Model	Insert Size	Overall Size	Viewable Area	Ships Via	Shipping Weight
TLES-1422	14" x 22"	15 3/8" x 23 3/8"	13" x 21"	FedEx	7

<sup>\*\*</sup>Make sure you laminate your insert material if going outdoors

<sup>\*\*</sup>Top Load Sign Frames are weather resistant...not water-proof