# OutdoorDisplayCases

A DIVISION OF ACCESS DISPLAY GROUP, INC.

TEL: 844-409-1134 FAX: 877-842-5126 E-MAIL: info@outdoordisplaycases.com

# **Product Sheet**

Item ID # LSIDMCLB-VA-1218

FOR CURRENT PRICING, VISIT THE ID # LISTED ABOVE

## 12" x 18" Outdoor Message Center Letter Board | LEFT Hinged - Single Door with Posts Information Board - SIZES REFER TO VIEWABLE AREA

### Product Details Outdoor Letter Board Message Center W SHOWIN 12 x 18 Viewing Window Are SENIOR FINE Standing Message Display Board Weather Resistant Display Case 11/2 - 12/2 4 Post Heights Selection: 3', 6', 8', 10' (3' and 6' heights only available for optional surface mount boots) Post Width: 4" x 4" Vinyl Letter Board Interior Panel Display important messages and protect them from the elements Overall size will vary based on orientation selected (see size chart below) Great for university campuses, parks, and golf courses Lockable door side mounted on a full-length piano LEFT-Hinged Will not rot, splinter, or crack with the high density polyethylene construction Finished back panel adds structural integrity Removable interior surface Locks included with two keys 3/4" wide main frame / 1 1/2' wide door frame 5 1/2" exterior depth / 3 3/4" interior depth 8 1/2" rain cover depth Exterior Cabinet Rain Shield (Roof Overhang) Withstands typical outside elements: Not flood or waterproof LED Illuminated display cases are Optional Posts should be secured at least 3 feet into the ground for proper support Optional Surface Mount Boot for installation on concrete or Hard surfaces (3' and 6' posts available for this option) Call to Customize Single Door Message Center Letter Board 145 piece 2" Helvetica letter / number set included Post Specifications & Ordering Options Optional vinyl grooved letterboards Optional letter & character sets (1/2", 3/4". 1", 2", 3") Single Post Information



- Post Width: 4" x 4" Post Height: 3', 6', 8' or 10' (3' and 6' heights only available for optional surface mount boots)
- Post is attached to the case through the bottom. Pre-drilled holes will be provided on the posts for easy display case mounting
- Post should be secured at least 3 feet into the ground for proper support.
- OPTIONAL: Surface Mount Boot for installation on concrete surfaces

### Recycled Plastic (Faux Wood) Construction Benefits

- Maintenance Free Recycled Plastic
- Will not crack or decay, split, rot or chip ٠
- Impervious to water, chemicals, and insects Finished back panel looks great and adds structural integrity

### Lighting Options

### LED LIGHTS - BRIGHTER & LONGER LASTING

Go GREEN with our energy saving LED Lights. Interior LED Lights are positioned on the interior to spotlight a wide range of information, including times, dates, menus, and other announcements. LED lights are long lasting, and energy efficient. Choose from Top Lit or Entire Interior Perimeter for LED Lighting placement.

- UL approved LED Strip Lighting
- Cool White LED Lighting
- LED Life: 50,000 hours

\*\*We provide a 3-wire cord attached to the ballast / transformer inside the display case. When installing you should use a licensed electrician / installer to bring power to the display. The installer will best decide where to exit the hardwire provided (we do not provide an exit hole as we feel it is best for the installer to decide the best exit point for power supply).

We offer TWO LED Lighting Options as detailed below:

TOP LIGHTING (ONE SIDE) For this option we place an LED strip light on the top side of the interior display case. The light will shine downward onto the interior case, highlighting the contents inside.

INSIDE PERIMETER (ALL 4 SIDES). For this option we place an LED strip light along the entire Perimeter of the interior display case. The light will shine from all 4 sides of the interior case, bringing more light intensity to the contents being displayed inside.

Model	Viewable Area	Overall Size (Portrait)	Overall Size (Landscape)	# of Posts	Shipping Wt.
LSIDMCLB-VA-1218	12" x 18"	18 3/4" Wide x 26 1/4" High	24 3/4" Wide x 20 1/4" High	1	105 LBS